

Application No.: 09/490,189

No.: BCS03656  
(PATENT)AMENDMENTS TO THE CLAIMS

1. (Cancelled).
2. (Currently amended) The method of Claim [[1]] 5 wherein transmitting the common synchronization signal from the burst manager includes transmitting the common synchronization signal in a downstream TDM signal over both downstream PON portions.
3. (Currently amended) A method of communicating between a burst manager and plural remote terminals over a first passive optical network (PON) and a second PON, each PON having a downstream  
portion and an upstream portion, the method comprising:  
transmitting a common synchronization signal from the burst manager to the  
plural remote terminals over both downstream PON portions;  
transmitting burst data from the plural remote terminals over both upstream PON portions to the  
burst manager, the burst data for each remote terminal being delayed on  
the first PON by a corresponding first delay and being delayed on the second PON by a  
corresponding second delay, the first delay comprising a first ranging delay and the second delay  
comprising a second ranging delay wherein the first and second ranging delays for each remote  
terminal are adjusted with respect to the common synchronization signal such that the burst data  
for any particular remote terminal transmitted on the first PON arrives at the burst manager  
simultaneously with the burst data for that particular remote terminal transmitted on the second  
PON. The method of Claim 1 wherein transmitting burst data includes transmitting burst data in TDMA timeslots such that corresponding timeslots on both PONs for each remote terminal are received at the burst manager aligned and in the same relative timeslot position and further

Application No.: 09/490,189

No.: BCS03656  
(PATENT)

comprising examining data received in the corresponding timeslots on both PONs at the burst manager to determine which timeslots contain valid data and selecting valid data on a per timeslot basis.

4. (Currently amended) The method of Claim [[1]] 3 wherein the first and second PONs are configured as counter-rotating quasi-rings.

5. (Currently amended) A method of communicating between a burst manager and plural remote terminals over a first passive optical network (PON) and a second PON, each PON having a downstream

portion and an upstream portion, the method comprising:

transmitting a common synchronization signal from the burst manager to the

plural remote terminals over both downstream PON portions;

transmitting burst data from the plural remote terminals over both upstream PON portions to the burst manager, the burst data for each remote terminal being delayed on

the first PON by a corresponding first delay and being delayed on the second PON by a

corresponding second delay, the first delay comprising a first ranging delay and the

second delay comprising a second ranging delay wherein the first and second ranging

delays for each remote terminal are adjusted with respect to the common synchronization

signal such that the burst data for any particular remote terminal transmitted on the first

PON arrives at the burst manager simultaneously with the burst data for that particular

remote terminal transmitted on the second PON. ~~The method of Claim 1~~ wherein the first

and second PONs are configured as uni-directional quasi-rings.

Application No.: 09/490,189

No.: BCS03656  
(PATENT)

6. Cancelled.
7. (Currently amended) The system of Claim [[6]] 10 wherein the burst manager transmits the common synchronization signal in a downstream TDM signal over both downstream PON portions.
8. (Currently amended) A communication system comprising:
  - a first passive optical network (PON) having a downstream portion and an upstream portion;
  - a second passive optical network (PON) having a downstream portion and an upstream portion;
  - a burst manager coupled to the first and second PONs, the burst manager transmitting a common synchronization signal over both downstream PON portions; and
  - a plurality of remote terminals coupled to the first and second PONs for communicating with the burst manager, each remote terminal transmitting burst data over both upstream PON portions to the burst manager, the burst data for each remote terminal being delayed on the first PON by a corresponding first delay and being delayed on the second PON by a corresponding second delay, the first delay comprising a first ranging delay and the second delay comprising a second ranging delay wherein the first and second ranging delays for each remote terminal are adjusted with respect to the common synchronization signal such that the burst data for any particular remote terminal transmitted on the first PON arrives at the burst manager simultaneously with the burst data for that particular remote terminal transmitted on the second PON.

The system of Claim 6 wherein the remote terminals transmit burst data in TDMA timeslots and the

Application No.: 09/490,189

No.: BCS03656  
(PATENT)

first and second ranging delays include a corresponding timeslot offset such that corresponding timeslots on both PONs for each remote terminal are received at the burst manager aligned and in the same relative timeslot position and wherein the burst manager examines data received in the corresponding timeslots on both PONs to determine which timeslots contain valid data and selects valid data on a per timeslot basis.

9. (Currently amended) The system of Claim [[6]] 8 wherein the first and second PONs are configured as counter- rotating quasi-rings.

10. (Currently amended) A communication system comprising:

a first passive optical network (PON) having a downstream portion and an upstream portion;

a second passive optical network (PON) having a downstream portion and an upstream portion;

a burst manager coupled to the first and second PONs, the burst manager transmitting a common synchronization signal over both downstream PON portions; and

a plurality of remote terminals coupled to the first and second PONs for communicating with the burst manager, each remote terminal transmitting burst data over both upstream PON portions to the burst manager, the burst data for each remote terminal being delayed on the first PON by a corresponding first delay and being delayed on the second PON by a corresponding second delay, the first delay comprising a first ranging delay and the second delay comprising a second ranging delay wherein the first and second ranging delays for each remote terminal are adjusted with respect to the

Application No.: 09/490,189

No.: BCS03656  
(PATENT)

common synchronization signal such that the burst data for any particular remote terminal transmitted on the first PON arrives at the burst manager simultaneously with the burst data for that particular remote terminal transmitted on the second PON. The system of Claim 6 wherein the first and second PONs are configured as uni-directional quasi-rings.

11. (New) The method of Claim 3 wherein transmitting the common synchronization signal from the burst manager includes transmitting the common synchronization signal in a downstream TDM signal over both downstream PON portions.
12. (New) The system of Claim 8 wherein the burst manager transmits the common synchronization signal in a downstream TDM signal over both downstream PON portions.